


SPECIFICATION SHEET


LumiSplit 2.10 and 1.6



LumiSplit 2.10



LumiSplit 1.6



CONNECTIVITY		
DMX INPUT	<ul style="list-style-type: none"> 4 x Neutrik 5 pin XLR (male) (2 at the front, 2 at the rear) 	<ul style="list-style-type: none"> 1 x Neutrik 5 pin XLR (male)
DMX OUTPUT	<ul style="list-style-type: none"> 10 x Neutrik 5 pin XLR (female) 	<ul style="list-style-type: none"> 1 x Neutrik 5 pin XLR (female) for thru connectivity
POWER	<ul style="list-style-type: none"> 1 x Neutrik PowerCON TRUE1 In/Out 	<ul style="list-style-type: none"> 1 x Neutrik PowerCON TRUE1 In/Out
DMX/RDM FEATURES		
SUPPORTED PROTOCOLS	<ul style="list-style-type: none"> DMX512 (1986 & 1990), DMX512-A, RDM ANSI E1.20 	<ul style="list-style-type: none"> DMX512 (1986 & 1990), DMX512-A, RDM ANSI E1.20
RDM DISCOVERABLE	<ul style="list-style-type: none"> Yes 	<ul style="list-style-type: none"> Yes
RDM FILTER PER INPUT	<ul style="list-style-type: none"> Yes, through input button 	<ul style="list-style-type: none"> Yes, through input button
RDM FILTER PER OUTPUT	<ul style="list-style-type: none"> Yes, available through the front panel and RDM 	<ul style="list-style-type: none"> Yes, available through RDM
DMX BACKUP MODE	<ul style="list-style-type: none"> Yes** 	<ul style="list-style-type: none"> No
HTP/LTP MERGER	<ul style="list-style-type: none"> Yes** 	<ul style="list-style-type: none"> No
REGENERATION MODE	<ul style="list-style-type: none"> Yes, available through the front panel and RDM** 	<ul style="list-style-type: none"> Yes, available through RDM**
DARK MODE	<ul style="list-style-type: none"> Yes, available through the front panel and RDM** 	<ul style="list-style-type: none"> Yes, available through RDM**
DMX ZONE SELECTION	<ul style="list-style-type: none"> Selection of the DMX zone per output 	<ul style="list-style-type: none"> No
USER PRESETS	<ul style="list-style-type: none"> 2, can be saved and recalled from the front panel** 	<ul style="list-style-type: none"> 2, available through RDM**
DMX PORT ISOLATION	<ul style="list-style-type: none"> Optic and galvanic isolation per port (except THRU) 	<ul style="list-style-type: none"> Optic and galvanic isolation per port (except THRU)
SHORT CIRCUIT PROTECTION	<ul style="list-style-type: none"> Yes 	<ul style="list-style-type: none"> Yes
TERMINATED OUTPUTS	<ul style="list-style-type: none"> Yes 	<ul style="list-style-type: none"> Yes
STATUS REPORT		
POWER	<ul style="list-style-type: none"> 1 x RGB LED on the front panel 	<ul style="list-style-type: none"> 1 x RGB LED on the front panel
DMX INPUT	<ul style="list-style-type: none"> 2 x RGB LED on the front panel 	<ul style="list-style-type: none"> 1 x RGB LED on the front panel
DMX OUTPUT	<ul style="list-style-type: none"> 10 x RGB LED on the front panel 	<ul style="list-style-type: none"> 6 x RGB LED on the front panel
LOCKABLE FRONT PANEL	<ul style="list-style-type: none"> Yes 	<ul style="list-style-type: none"> Yes
POWER		
POWER INPUT	<ul style="list-style-type: none"> 100 – 240V AC; 16A; 50-60Hz 	<ul style="list-style-type: none"> 100 – 240V AC; 16A; 50-60Hz
POWER OUTPUT	<ul style="list-style-type: none"> MAX 15A 	<ul style="list-style-type: none"> MAX 15A
POWER CONSUMPTION	<ul style="list-style-type: none"> 100-240V AC, 0,2-0,1A; 50-60Hz 	<ul style="list-style-type: none"> 100-240V AC, 0,2-0,1A; 50-60Hz
FUSE	<ul style="list-style-type: none"> No user-serviceable fuse 	<ul style="list-style-type: none"> No user-serviceable fuse
PHYSICAL		
DIMENSION (WXDXH)	<ul style="list-style-type: none"> 482 x 204.85 x 44 mm 	<ul style="list-style-type: none"> 303 x 210 x 44 mm (with ears: 482 x 210 x 44 mm)
WEIGHT	<ul style="list-style-type: none"> 2,54 kg 	<ul style="list-style-type: none"> (t.b.d.)
PACKAGING	<ul style="list-style-type: none"> 530 x 330 x 80 mm 	<ul style="list-style-type: none"> 530 x 330 x 80 mm
ENVIRONMENTAL		
OPERATING TEMPERATURE	<ul style="list-style-type: none"> 0 to 50°C 	<ul style="list-style-type: none"> 0 to 50°C
STORAGE TEMPERATURE	<ul style="list-style-type: none"> -10 to 70°C 	<ul style="list-style-type: none"> -10° to 70°C
HUMIDITY	<ul style="list-style-type: none"> 5 to 95% 	<ul style="list-style-type: none"> 5 to 95%
APPROVALS		
CERTIFICATIONS	<ul style="list-style-type: none"> CE, RoHS Compliance, FCC Part 15*, CFR 47*, Class A* 	<ul style="list-style-type: none"> CE, RoHS Compliance, FCC Part 15*, CFR 47*, Class A*
STANDARDS	<ul style="list-style-type: none"> UL 60950-1*, CAN/CSA-C22.2 No.60950-1*, CAN/ICES-003(A)*, IEC 60950-1*, EN 60950-1, EN55022 (CISPR22), EN55024 (CISPR24) 	<ul style="list-style-type: none"> UL 60950-1*, CAN/CSA-C22.2 No.60950-1*, CAN/ICES-003(A)*, IEC 60950-1*, EN 60950-1, EN55022 (CISPR22), EN55024 (CISPR24)

* Pending, ** Available in a future firmware upgrade