


# EclPanel TWC

740W Tunable White and colourful LED soft light with pixels and lighting effects (driven @ 430W)

ORDER CODE: **ECLPANELTWC**



**EclPanel TWC**, is the compact 2x1 LED soft light that provides a beautiful, wide source of soft and precise colours. In addition to this, the PROLIGHTS **EclPanel TWC** comes with a full range of white reproductions, from daylight through to tungsten tones, reaching a superior light quality with high CRI, TLCI and TM-30. The **EclPanel TWC** allows for quick and accurate local adjustment of light through 3 rotatory knobs with three fully featured modes: CCT with +/- green shift, HSI for total control of hue, saturation and intensity, FX mode to access the on board pixel cinema effects. The unit can also be controlled on a per-section basis, allowing for reproduction of onboard customisable effects or to be self-made through the lighting desk. Both methods provide eye-candy, with the appealing and modern front looks and cinematic special effects. The unit is designed with an onboard driver and built-in power supply and, being lightweight, the **EclPanel TWC** offers easy rigging and cabling making it the perfect lighting tool for every location.

## MAIN FEATURES

- 740W RGB + Warm White Led source (driven @430W)
- CRI > 95,5; R9 > 92; TLCI > 92
- 8 section pixel control and built-in lighting effects for Cinema applications
- Silent operation with multiple fan modes
- Battery connection (4pXLR 24-36V): compatible with industry standard external batteries (optional)

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 740W RGB + Warm White LEDs (driven @ 430W)
- Luminous flux: 34'236lm @4.000 K with MD filter
- Lux: @4000K, 517lx @5 m
- CRI: 94,6 @3.200 K; 95,5 @5.600 K
- R9: 97 @3.200 K; 92 @5.600 K
- TLCI: 92 @5.600 K
- TM30 Rf: 92 @3.200 K; 89,5 @5.600 K
- TM30 Rg: 103 @3.200 K; 102,4 @5.600 K
- Source life expectancy: > 50.000 h

### OPTICS

- Beam angle: 102°
- Field angle: 159°
- Lens type: Medium Density diffusion panel (interchangeable)
- Additional optics: see available accessories

### COLOUR SYSTEM

- Colour control: XY, CCT, RGBW, Gel, HSI, Source Emulation, Color Macros, CTO on colors
- Colour mixing: RGB + Warm White
- CCT: CCT control range from 2.200K to 15.000K, + / - green correction, tungsten emulation
- White presets: 2.800K - 10.000K with 28 K resolution
- Colour wheel: virtual colour wheel with macros
- Macros: Gels library on-board

### DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer, colours
- Pixel patterns: pre-programmed pixel macros and cinema lighting effects patterns
- Special features: linear crossfade channel from any white to any colour; virtual CTO on colours

### BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

### CONTROL

- Protocols: DMX512, RDM, W-DMX, rotatory knob
- Stand Alone: selectable mode through 3 rotatory knobs
- Pixel control: 8 section control
- Wireless Control: included, Wireless Solution transceiver
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: selectable dimming modes available
- Strobe / shutter: 1 - 30 Hz, electronic
- Display battery: self-charging battery backup
- Operating temperature: -10° ~ +45°
- LED Control: flicker free frequency with adjustable PWM
- Selectable PWM: 600 ~ 36.000 Hz

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Low Voltage DC mains: 24-36V
- Max power consumption: 460W
- Power factor: >0,94

### PHYSICAL

- IP rating: 20
- Cooling: active, silent operation
- Suspension and fixing: bracket for hanging and positioning
- Signal connection: Amphenol XLR 5p IN/OUT connectors
- Power connection: Neutrik powerCON TRUE1 IN/OUT connectors
- Low Voltage DC connector: XLR 4p
- Dimensions (WxHxD): 819x431x144 mm / (with PO system) 836x431x144mm
- Weight: 15,3 / (with PO system) 17,1kg


### CERTIFICATIONS / APPROVALS

- CE, cTUVus, UKCA

## ACCESSORIES & RELATED PRODUCTS

• 9513FXWL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, MENAC3FXW socket, L.3 m	• EPTWCBDR2	Barn door with 4 directional flaps to adjust the light beam
• 9533FXWL03	Ass. 3x2.5mm TH07 cable, SHUKO plug, MENAC3FXW socket, L.3m	• EPTWCBSB21	SnapBag 2x1 for ECLPANELTWC by DoP choice
• 958225L03	3x2.5mm TH07 Cable, 16A 3p PwCon MXW, 16A 3p PwCon FXW, L. 3m	• EPTWCSCG4SB2140	40° SnapGrid for SnapBag, 2x1 for ECLPANELTWC by DoP choice
• C6002B	Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black	• EPTWCSCG2140	40° SnapGrid, 2x1 for ECLPANELTWC by DoP choice
• C6040B	Aluminum clamp for 28mm spigot, 200kg load, 48-51mm tubes, black	• EPSRER	Rabbit-Ears 2x1 Rectangular for ECLPANELTWC by DoP choice
• RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black	• EPSBRL3	Snapbag Lantern 3' for Rabbit-Ears by DoP. Incl. Lantern, Backcovers, Carry Bag
• TOUR53415L03	Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m	• EPSBRL3C4	Cover for Snapbag Lantern 3' (EPSBRL3) by DoP choice; 4 sides, adj. with zipper
• WSBBF1G5	BlackBox F-1 G5 transmitter, 2,45GHz & 5.2/5,8 GHz, DMX/RDM, 512Ch	• EPSBRM	SnapBag Medium to be mounted on Rabbit Ears by DoP.
• WSBBF1G6	BlackBox F-1 G6 transrec, 512ch, 2.45GHz, DMX&RDM,Bluetooth,G3,G4,G4S, G5, CRMX	• EPSGCM40	40° SnapGrid, to be mounted on Snap Bag Medium (EPSBRM)
• WSBBR512G5	BlackBox R-512 G5 receiver 512Ch, 2.45GHz & 5.8GHz, DMX/RDM optional	• EPSBRO3	Snapbag Octa 3' to be mounted on Rabbit-Ears by DoP.
• WSBBR512G6	BlackBox R-512 G6 receiver 512Ch, 2.45GHz,DMX&RDM,Bluetooth,G3,G4,G4S,G5,CRMX	• EPSGC3W40	40° SnapGrid, to be mounted on Snap Bag Octa 3' (EPSBRO3)
• FCLPANEL1U	Flight case for 1 pc of ECLPANELTWC	• EPSBRO5	Snapbag Octa 5' to be mounted on Rabbit-Ears by DoP.
• FCLPANEL3U	Flight case for 3 pcs of ECLPANELTWC	• EPSGC5W40	40° SnapGrid, to be mounted on Snap Bag Octa 5' (EPSBRO5)
• ECLPANELPOYO	Pole operated aluminium yoke bracket for ECLPANELTWC	• EPSBRO7	Snapbag Octa 7' to be mounted on Rabbit-Ears by DoP.
• EPTWCBAG1U	Trolley bag for 1 pc of ECLPANELTWC	• EPSGC7W40	40° SnapGrid, to be mounted on Snap Bag Octa 7' (EPSBRO7)
• EPTWCRC	Rain Cover for ECLPANELTWC	• EPSBCFNSM	Diffusion MAGIC cloth for Snapbag 60x90cm (EPTWCBSB21) by DoP choice
• EPTWCFILTERINT	Front intensified diffusion filter for ECLPANELTWC	• EPSBCFNFS	Diffusion FULL Grid cloth for Snapbag 60x90cm (EPTWCBSB21) by DoP choice
• EPTWCFILTERHD	Front high diffusion filter (less output) for ECLPANELTWC	• EPSBCFNFSH	Diffusion HALF Grid cloth for Snapbag 60x90cm (EPTWCBSB21) by DoP choice
• EPTWCFILTERMD	Front medium diffusion filter for ECLPANELTWC	• EPSBCFNFSQ	Diffusion QUARTER Grid cloth for Snapbag 60x90cm (EPTWCBSB21) by DoP choice
• EPTWCFILTERLD	Front low diffusion filter (more output) for ECLPANELTWC	• EPSBCFNFSQFM	Diffusion cloth SET(1/4,1/1,MAGIC) for Snapbag 60x90cm (EPTWCBSB21) by DoP choice
• ECLFRSPG	Spigot for PROLIGHTS fixtures	• EPSBCFNFSQH	Diffusion cloth SET (1/4, 1/2,1/1) for Snapbag 60x90cm (EPTWCBSB21) by DoP choice
• EPTWCEC30	30 degree egg crate for ECLPANELTWC	• EPTWCLANT21	Snapbag Lantern for ECLPANELTWC by DoP. Incl. Lantern, Backcovers, Carry Bag
• EPTWCEC60	60 degree egg crate for ECLPANELTWC	• SWIT500W2KIT	24/48V 500W battery (>1.2hrs) KIT including 2*PBH260S smart power batt.+st.adapt
• EPTWCEC8C	8 chamber egg crate for ECLPANELTWC	• UPBOX1U	Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT
• EPTWCBD	Barn door with 4 directional flaps to adjust the light beam		

## TECHICAL DRAWINGS



For more product info and downloads visit our website

