

Artistic Licence (UK) Ltd.



Certificate of Fire Safety

The Product **Pixi-Web (also known as Color Web)** has been designed to meet or exceed ULV0 fire safety standard.

The Webbing Material is constructed of Polyester Fibre & Resin.

Original manufacturer tests are attached to this document.

Issued by Artistic Licence (UK) Ltd. on
1/11/2005
Signatory:

Wayne D Howell

Managing Director

Material Safety Data Sheet**Polyester Fiber and Resin****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME Standard PET, DSP*, 1X30, 1X40, 1X50, 1X90, 1X98, 1W60, 1W70, 1W72, 1W76, 1W77, 1W78, 1Y86, 1Y87, (Non Adhesion Activated)
OTHER/GENERIC NAMES: Polyester Fiber and Resin
PRODUCT USE: Industrial fiber or resin. If the fiber is to be used for special applications, e.g., in the food handling industry, or in the medical or surgical sector, please contact Honeywell to determine the suitability of the intended use.

MANUFACTURER: Honeywell
 Performance Fibers
 101 Columbia Road
 Box 1053
 Morristown, New Jersey 07962-1139

FOR MORE INFORMATION CALL:
 (Monday-Friday, 9:00am-4:30pm)
 1-800-707-4555

IN CASE OF EMERGENCY CALL:
 (24 Hours/Day, 7 Days/Week)
 1-800-707-4555

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS NUMBER	WEIGHT %
Polyethylene terephthalate	25038-59-9	> 98

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Solid off white or delustered yarn or fiber. Chips have clear to greenish tint. There are no hazards associated with the product for which first aid is required.

POTENTIAL HEALTH HAZARDS

SKIN: May cause mechanical irritation.

EYES: May cause mechanical irritation.

INHALATION: Not respirable in this form. Thermal processing of fiber may generate fumes and vapors which may cause irritation to the nose and throat. Dust should be considered as a nuisance dust (see Section 8).

INGESTION: Not a probable route of exposure.

DELAYED EFFECTS: None known.

MATERIAL SAFETY DATA SHEET

Polyester Fiber and Resin

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

<u>INGREDIENT NAME</u>	<u>NTP STATUS</u>	<u>IARC STATUS</u>	<u>OSHA LIST</u>
No ingredients listed in this section.			

4. FIRST AID MEASURES

SKIN: If irritation develops, wash affected area with soap and water. If discomfort continues, obtain medical attention.

EYES: If irritation develops, flush eyes with running water. If discomfort continues, obtain medical attention.

INHALATION: If processing vapor occurs and irritation develops, remove person to fresh air. If discomfort persists, seek medical attention.

INGESTION: Not a probable route of exposure.

ADVICE TO PHYSICIAN: No specific advice. Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT:	Not applicable
FLASH POINT METHOD:	Not applicable
AUTOIGNITION TEMPERATURE:	500° C (Layer Ignition Temperature)
UPPER FLAME LIMIT (volume % in air):	Not applicable
LOWER FLAME LIMIT (volume % in air):	Not applicable
FLAME PROPAGATION RATE (solids):	Not determined
OSHA FLAMMABILITY CLASS:	Not applicable

EXTINGUISHING MEDIA:
All standard agents may be used.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
None.

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:
Wear self-contained breathing apparatus. Avoid excessive inhalation of smoke or potential thermal decomposition products.

6. ACCIDENTAL RELEASE MEASURES

IN CASES OF SPILL OR OTHER RELEASE: (Always wear recommended personal protective equipment.)
Sweep or vacuum and place in containers for disposal to an approved landfill or reuse.

MATERIAL SAFETY DATA SHEET

Polyester Fiber and Resin

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

7. HANDLING AND STORAGE

NORMAL HANDLING: (Always wear recommended personal protective equipment.)
No special handling requirements.

STORAGE RECOMMENDATIONS:
No special storage requirements.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:
Mechanical ventilation should be used during processing to remove any dusts, mists, or vapors, which may be generated.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION:
Protect against potential physical hazards such as contact with yarn moving at high speed, etc.

EYE PROTECTION:
Safety glasses are recommended during processing.

RESPIRATORY PROTECTION:
None normally required. An approved dust respirator meeting 42 CFR Part 84 standard should be worn if dusty conditions exist.

ADDITIONAL RECOMMENDATIONS:
None required.

EXPOSURE GUIDELINES (Guidelines exist for the following ingredients)

<u>INGREDIENT NAME</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER LIMIT</u>
------------------------	------------------	-----------------	--------------------

* No ingredients listed in this section *

- * = Limit established by Honeywell International, Inc.
- ** = Workplace Environmental Exposure Level (AIHA).
- *** = Biological Exposure Index (ACGIH).

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

Dust should be considered a nuisance dust:
ACGIH TLV: 10 mg/m³ total dust
OSHA PEL: 15-mg/m³ total dust; 5-mg/m³ respirable dust

See Section 16 regarding finish mists.

MATERIAL SAFETY DATA SHEET

Polyester Fiber and Resin

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	off white solid or delustered fiber or clear to greenish resin
PHYSICAL STATE:	Solid
MOLECULAR WEIGHT:	>30,000
CHEMICAL FORMULA:	(C ₁₀ H ₈ O ₄) _x
ODOR:	No specific odor.
SPECIFIC GRAVITY (water = 1.0):	1.3 - 1.4 g/cm ³
SOLUBILITY IN WATER (weight %):	Insoluble
pH:	Not applicable
BOILING POINT:	Not determined
MELTING POINT:	260 °C
VAPOR PRESSURE:	Not applicable
VAPOR DENSITY (air = 1.0):	Not applicable
EVAPORATION RATE:	Not applicable
% VOLATILES:	Not applicable
FLASH POINT:	Not determined

COMPARED TO: Not applicable

(Flash point method and additional flammability data are found in Section 5.)

10. STABILITY AND REACTIVITY

NORMALLY STABLE? (CONDITIONS TO AVOID):

Normally stable

INCOMPATIBILITIES:

Tends to dissolve in caustic materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition products may include CO, ethylene glycol, aldehydes and other C, H, and O compounds varying in chemical structure and molecular weights.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

IMMEDIATE (ACUTE) EFFECTS:

Not considered to cause irritant or allergic contact dermatitis based on testing results for skin irritation (rabbits), skin sensitization (guinea pig), and clinic evaluation using repeated insult patch test.

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Not Available

OTHER DATA:

MATERIAL SAFETY DATA SHEET

Polyester Fiber and Resin

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS**RCRA**

Is the unused product a RCRA hazardous waste if discarded? NO
If yes, the RCRA ID number is: Not applicable

OTHER DISPOSAL CONSIDERATIONS: Dispose of as nonhazardous waste.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME:
US DOT HAZARD CLASS: Not regulated
US DOT ID NUMBER: Not applicable

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

15. REGULATORY INFORMATION**TOXIC SUBSTANCES CONTROL ACT (TSCA)**

TSCA INVENTORY STATUS: Polymer is listed on the TSCA Inventory.
OTHER TSCA ISSUES: None

SARA TITLE III / CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

INGREDIENT NAME	SARA/CERCLA RO (lb.)	SARA EHS TPO (lb.)
No Ingredients listed in this section.		

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-9802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: No Ingredients listed in this section

SARA 313 TOXIC CHEMICALS:

The following ingredients are SARA 313 "Toxic Chemicals". CAS numbers and weight percents are found in Section 2.

MATERIAL SAFETY DATA SHEET

Polyester Fiber and Resin

INGREDIENT NAME

No ingredients listed in this section

COMMENT

STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME

No ingredients listed in this section

WEIGHT % COMMENT

ADDITIONAL REGULATORY INFORMATION:

None.

WHMIS CLASSIFICATION (CANADA):

Not a controlled product.

FOREIGN INVENTORY STATUS:

Not determined.

16. OTHER INFORMATION

CURRENT ISSUE DATE: July, 2002

PREVIOUS ISSUE DATE: February 10, 2001

CHANGES TO MSDS FROM PREVIOUS ISSUE DATE ARE DUE TO THE FOLLOWING:

Updated product information and contact information

OTHER INFORMATION: Polyester Fibers are coated with minor quantities of finish oils. Textile processes may volatilize portions of these finishes and produce visible misting in the workplace. Ventilation is recommended to minimize exposure to such finish mists which should not exceed a concentration of 5 mg/m³ (ACGIH TLV for mineral oil)