



Chroma-Q®
BRILLIANT SOLUTIONS

Specification Sheet - Version: 1.3 US
Chroma-Q® 2inspire™ 100/200/300 POE
Part No: CQ150X-10ZZ



DESCRIPTION

The new Chroma-Q® 2inspire™ family delivers truly flexible lighting into any space quickly and efficiently.

2inspire™ is a compact, silent, bright fixture, available in 3 sizes. These installation luminaires deliver studio-grade tuneable white light and pure theatrical quality colors.

A holistically designed accessory collection easily mounts each fixture - on a wall, as a pendant, in a ceiling or from a yoke.

Innovative technology minimises deployment costs and maximises efficiency, making every 2inspire™ flexible, sustainable and durable.

FEATURES

- RGB-CW-WW colour system for an extended color rendering
- Ethernet POE connection
- 900, 1400, 3100 lumens
- Multiple mounting accessories

ORDERING INFORMATION

- CQ150X-1000: 2inspire POE RGBWWCW IP20 black body
- CQ150X-1005: 2inspire POE RGBWWCW IP20 white body
- CQ150X-1010: 2inspire POE RGBWWCW IP65 black body
- CQ150X-1015: 2inspire POE RGBWWCW IP65 white body

ACCESSORIES

- CQ1509-9001 Wall mount black
- CQ1509-9002 Wall mount white
- CQ1509-9011 Pendant mount kit (w/o stem, w/o yoke) black **
- CQ1509-9012 Pendant mount kit (w/o stem, w/o yoke) white **
- CQ1509-9X11 Shroud for pendant mount kit black**
- CQ1509-9X12 Shroud for pendant mount kit white**
- CQ1509-9017 Pendant stem 1ft, 300mm black
- CQ1509-9018 Pendant stem 1ft, 300mm white
- CQ1509-9021 Pendant stem 2ft, 600mm black
- CQ1509-9022 Pendant stem 2ft, 600mm white
- CQ1509-9026 Pendant stem 3ft, 900mm black
- CQ1509-9027 Pendant stem 3ft, 900mm white
- CQ1509-9X06 Yoke black**
- CQ1509-9X07 Yoke white**



Accessories (cont'd)

- CQ1509-9X37 Blind Ceiling Mount Flush 0o black**
- CQ1509-9X38 Blind Ceiling Mount Flush 0o white**
- CQ1509-9X41 Blind Ceiling Mount Recessed 0o black*
- CQ1509-9X42 Blind Ceiling Mount Recessed 0o white**
- CQ1509-9Y21 Blind Slant Ceiling Mount 0o Black***
- CQ1509-9Y22 Blind Slant Ceiling Mount 0o White***
- CQ1509-9Y26 Blind Slant Ceiling Mount 0-25o Black***
- CQ1509-9Y27 Blind Slant Ceiling Mount 0-25o White***
- CQ1509-9Y31 Blind Slant Ceiling Mount 25-45o Black***
- CQ1509-9Y32 Blind Slant Ceiling Mount 25-45o White***
- CQ1509-9X36 Honeycomb louver black**
- CQ1509-9X37 Honeycomb louver white**
- CQ1509-9X41 Barndoor black**
- CQ1509-9X42 Barndoor white**
- CQ1509-9X46 Snoot black**
- CQ1509-9X47 Snoot white**
- CQ1509-9X51 Medium diffusion (pack of 10)**
- CQ1509-9X56 Wide diffusion (pack of 10)**
- CQ1509-9X61 Extra wide diffusion (pack of 10)**
- CQ1509-9X66 Assymetrical diffusion (pack of 10)**
- CQ1509-9X71 Gel holder C ring BK**
- CQ1509-9X72 Gel holder C ring WH**

** replace X by 1=2inspire 100, 2=2inspire 200, 3=2inspire 300

*** replace Y by 2=2inspire 200, 3=2inspire 300

www.chroma-q.com



Chroma-Q[®]
BRILLIANT SOLUTIONS

Specification Sheet - Version: 1.3 US
Chroma-Q[®] 2inspire™ 100/200/300 POE
Part No: CQ150X-10ZZ

OVERALL SPECIFICATIONS

2inspire™ 100

Net Dimensions (without fixings): W: 93mm x H: 93mm x D: 108mm
W: 3.7" x H: 3.7" x D: 4.3"
Net Weight: 0.62kg / 1.4lb

2inspire™ 200

Net Dimensions (without fixings): W: 118mm x H: 118mm x D: 145mm
W: 4.7" x H: 4.7" x D: 5.7"
Net Weight: 1.15kg / 2.5lb

2inspire™ 300

Net Dimensions (without fixings): W: 147mm x H: 147mm x D: 195mm
W: 5.8" x H: 5.8" x D: 7.7"
Net Weight: 2.5kg / 5.1lb

Color mixing: RGB WW CW
Color Temp Control: Variable 2400 - 6500K
Tint Control: -2 to +2
Control Protocol: Artnet / sACN / RDM
RDM compliance: Yes
LED Pixels: 1
Control Modes: I single channel intensity
IK intensity and CCT
IKT intensity, CCT, tint
RGB RGB+magic white
IRGB intensity and RGB+magic white
IHS intensity, hue and saturation+magic white
IKTRGB intensity, CCT, tint, RGB+magic white
IKTHS intensity, CCT, tint, hue, saturation+magic white
RGB-WW-CW RGB warm-white and cold-white

DMX Channels: 1 to 13
Dimming Curve: Linear, Inverse square-law, square-law, S-curve
Setting and Addressing: Through Art-Net RDM
Hot Lumen Output: 900 / 1400 / 3100 lumens
Optics: Fully homogenised
Beam Angle: 21° / 19° / 27° (approx)
Optional Diffusion: 36, 65, 80, Assymetrical (approx)
Beam Distribution: Symmetrical
Colour Engine: Gen3 ColorSure™ calibrated engine
CCT: 2400-6500K
Colour Gamut Ratio: sRGB=151%; NTSC=107%; AdobeRGB=112%;
DCI-P3=112%;REC.2020=80%

CRI: >90
TLCI: >90

IES TM-30-18 Rf >90
IES TM-30-18 Rg <100 to 103
Lamp Life: <L70 50,000hr

Power & Data
Connector In: RJ45 Ethernet POE
Mounting points: Multi
Orientation: Any
Construction: Powder coated black aluminum cast
Powder coated white aluminum cast

Colour: Black RAL 9005/ White RAL 9010
IP Rating: IP20 / Optional IP65
Power Supply: 802.3at / 802.3bt Class A / Class B
Power Input Rating: 50-57 VDC
Max Power Consumption: 20W / 40W / 60W
Idle Power Consumption: 3W
Cooling System: Natural Convection
Max Surface Temperature: Ta=60°C
Operating Temperature: -20°C to 40°C
Total heat dissipation: 69 / 137 / 205 BTU/hr

Approvals: CISPR 22 :2006/EN55022 :2006 & CISPR 24 :1997/EN55024 :1998; ICES-003 :2004 & FCC Part 15 Subpart B: 2007; CSA C22. No. 166-M1983:R2008; UL 1573:2003; UL 8750



www.chroma-q.com

Chroma-Q and all associated product names are recognised trademarks, for more information visit www.chroma-q.com/trademarks. The rights and ownership of all trademarks are recognised. Whilst every effort has been made to ensure that the information is correct, Chroma-Q accepts no liability for errors or omissions. Technical specifications and data are provided for guidance only. Because we constantly aim to improve our products, we reserve the right to amend or alter at any time and without prior notice, the specifications of any product. E&OE.