



**Chroma-Q®**  
BRILLIANT SOLUTIONS

**Specification Sheet - Version: 1.0**

**Chroma-Q® The Force Multi-tool**

**Part No: CQ1527-1000**

“Chroma-Q The Force”, the versatile multi-tool designed for the dedicated lighting professional. This robust device streamlines the firmware update process across a wide range of Chroma-Q products, including the 2inspire series. With the capacity to store numerous firmware versions for various products, “Chroma-Q The Force”, ensures that your equipment is always up-to-date, whether through RS485 or Ethernet connections. Additionally, its RDM management capabilities allow for remote addressing and configuration of RDM-compatible devices, while the integrated DMX viewer provides real-time monitoring of DMX signals, making it an indispensable tool for service centers, rental shops, and road crews alike.

**FEATURES**

- Multi-Product Firmware Storage: “Chroma-Q The Force”, can hold various firmware revisions for a multitude of Chroma-Q products simultaneously.
- Dual Update Compatibility: Offers both RS485 and Ethernet firmware updates, providing flexibility in connectivity and use.
- RDM Management: Equipped with RDM manage tools for remote addressing and adjustments on RDM compatible devices.
- DMX Signal Monitoring: Features a DMX viewer to observe and diagnose DMX signal integrity in real-time.
- User-Friendly Interface: Designed with a straightforward interface for easy navigation and operation by professionals.
- Portable Design: Crafted for convenience, its compact and durable design makes it ideal for on-the-go technicians and roadies.

**SPECIFICATIONS**

Net dimensions:	Width: 180mm / 7.1” Height: 84mm / 3.3” Depth: 136mm / 5.35”
Net weight:	1.2kg / 2.5lbs
Shipping dimensions:	Width: 256mm / 10” Height: 130mm / 5.12” Depth: 220mm / 8.66”
Shipping weight:	1.79kg / 3.95lbs
Colour:	Dark Grey
IP Rating	IP20
Cooling System	Convection
Operating Temperature	0°C to 40°C
Construction	Powder-coated steel
Control Protocol	Artnet, sACN, DMX
Power Input:	DC USB-C PD or PoE AF
Power Input Rating	9-12VDC for USB C input / 44-57 VDC for PoE input
Power Consumption	5W
Rated input current	0.6A
Idle Power Consumption	5W
Power connector:	USB-C / RJ45
Ethernet connector In:	RJ45
DMX connector Out:	XLR5 F
DMX connector In:	XLR5 M
Data to PC	USB Type B
Data to External drive	USB Type A
SB-C PD supply	Included
USB-C PD Cable	Included

“Chroma-Q The Force: The Technician's Essential Companion”



**ORDERING INFORMATION**

CQ1527-1000:Chroma-Q The Force multi-purpose tool

